

Measurement Unlimited by The Imagination.

Portable Ultrasonic Flowmeter

UFP-20



intelligent
DIGITAL

Features

1. Multi-flow Measurement Function

Easy configurable for 2-channel or 2-path measurement

2. Energy Meter Function

Energy flow rate measurement with Pt-100 RTD option

3. Receiving-echo Monitor Function

Visual confirmation whether receiving echo is "Good" or "No good"

4. Weather-proof structure IP65

IP65 rating maintained even during measurement

5. USB Memory Data Transfer

Logged data in UFP-20 can be transferred via USB memory device to a PC.


Specifications

Measurement	Method	Ultrasonic pulse transit time difference method		
	Diameter Range	DN 13mm ~ 5000mm		
	Accuracy	Pipe Diameter	Velocity \geq 1m/s	Velocity < 1m/s
		DN 13mm (*2) ~ 90mm (DN 20mm ~ 50mm) (*1)	$\pm 2.0\%$ R.D. ($\pm 2.0\% \sim \pm 5.0\%$) (*1)	$\pm 0.02\text{m/s}$ R.D. ($\pm 0.02\text{m/s} \sim \pm 0.05\text{m/s}$) (*1)
DN 100mm ~ 250mm DN 300mm ~ 5000mm		$\pm 1.5\%$ R.D. $\pm 1.0\%$ R.D.	$\pm 0.015\text{m/s}$ $\pm 0.01\text{m/s}$	
Transducer		Applicable Diameter	Applicable Temperature	
	Small Transducer	DN 13mm ~ 50mm	$-20^{\circ}\text{C} \sim 120^{\circ}\text{C}$	
	Medium Transducer	DN 65mm ~ 500mm (DN 20mm ~ 50mm) (*1)	$-20^{\circ}\text{C} \sim 120^{\circ}\text{C}$	
	Large Transducer	DN 300mm ~ 5000mm	$-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$	
	Cable Length	7m as standard (157m Max. Extendable)		
Output	Analog Output	1port; 4 - 20mA Allowable load resistance 550 Ω Max.		
Temperature Input	4pcs of RTD (Pt - 100) as Max.			
Data Logging	Internal logged data transferred through USB memory in CSV format			
Function	EASY interfacing with Installation Wizard Self - diagnostics Low flow cut Zero shift Span compensation 2 - channel / 2 - path measurement (with additional pair of transducers) Thickness meter function (Range; 1mm ~ 100mm / Accuracy; $\pm 0.1\text{mm}$ or $\pm 1.5\%$ R.D.)		Sonic Velocity measurement function (Range; 500m/s ~ 3000m/s / Accuracy; $\pm 5\%$) Filtering Echo - wave form monitor Multi - language support (English, French, German, Italian, Portuguese, Russian, Spanish, Turkish) Metric / English (inch, gallon or barrel) units selectable	
Protection degree	IEC 60529 Protection Degree IP65 (Main Unit and Transducers)			
Internal Battery	8 hours as Max. / Rapid charging 4 hours			

(*1): Medium transducer is recommended for measurement of DN 20mm ~ 50mm pipe which attenuates sonically like Zinc - coated - pipe.

(*2): Site calibration will be required.

Design and specifications are subject to change without prior notice, and without any obligation on the part of the manufacturer.



TOKYO KEIKI INC.

www.tokyo-keiki.co.jp/ryutai/

Control Division I Fluid Management Systems SBU

Head Office

2-16-46, Minami-Kamata, Ohta-ku, Tokyo 144-8551 JAPAN TEL. +81-3-3737-8664 FAX. +81-3-3737-8665

September 2011 Cat.No.1415-1-E-3-H